

# Flow Measurement

## SITRANS F US Clamp-on

SITRANS FST020 (Basic)

### Overview



SITRANS FST020 offers reliable flow measurement at a much lower cost than other clamp-on ultrasonic flowmeters, with flow rate accuracy of  $\pm 0.5\%$  to  $1.0\%$  for most applications.

### Benefits

- Easy installation; no need to cut pipe or stop flow
- Minimal maintenance; external sensors do not require periodic cleaning
- No moving parts to wear or foul
- No pressure drop or energy loss
- Compact, integral design reduces installation cost
- Wide turn-down ratio
- Optional WideBeam technology ensures high performance.
- ZeroMatic Path automatically sets zero without stopping flow and eliminates zero drift.

### Application

SITRANS FST020 is suitable for most clean liquid applications, including the following:

- Water & wastewater industry
  - Potable water
  - Wastewater, influent & effluent
  - Processed sewage, sludge
- Chemical feed industry
  - Sodium hypochlorite
  - Sodium hydroxide
- HVAC & power industries
  - Coolant flow
  - Fuel flow
- Process control
  - Chemicals
  - Pharmaceuticals

The SITRANS FST020 flowmeter is not available with hazardous areas approval.

### Design

- IP65 (NEMA 4X) wall mount constructed of polycarbonate
- Single channel versions only

### Function

- 2 x 16 integral alphanumeric display and 5 key keypad for installation menu and data display
- Pulse rate output
- RS 232 digital communication port with a DB9 connector, Modbus and BACnet
- Totalizer start/stop and rest control lines.
- Remote PC installation menu
- ZeroMatic Path automatically sets zero
- Bidirectional flow operation
- 1 MByte data logger with both site & data logger storage
- Menu language in English, Spanish, German, Italian and French

### Technical specifications

<b>Input</b>	
Flow range	$\pm 12$ m/s ( $\pm 40$ ft/s), bi-directional
Flow sensitivity	0.0003 m/s (0.001 ft/s) flow rate independent
<b>Digital Inputs</b>	
Totalizer Hold	Optically isolated diode Input voltage: 2 ... 10 V DC
Totalizer Reset	Optically isolated diode Input voltage: 2 ... 10 V DC
<b>Output</b>	
Current	<ul style="list-style-type: none"> <li>• 4 ... 20 mA (Isolated)</li> <li>• externally powered 10 ... 30 V DC</li> </ul>
Relay	<ul style="list-style-type: none"> <li>• Programmable Form C 250 mA</li> <li>• 30 V DC</li> <li>• 3 V A max</li> </ul>
Pulse rate <sup>1)</sup>	<ul style="list-style-type: none"> <li>• Optically isolated transistor 10 mA</li> <li>• 30 V DC max</li> </ul>
<b>Accuracy</b>	
• 4 ... 20 mA	For velocities $\geq 0.3$ m/s (1 ft/s) $\pm 1.0\%$ ... $2.0\%$ of flow
• Pulse, relay output	$\pm 0.5\%$ ... $1.0\%$ of flow
Batch repeatability	$\pm 0.15\%$
Zero Drift	0.1 % of rate; 0.0003 m/s (0.001 ft/s)
Data refresh rate	5 Hz
<b>Transmitter conditions</b>	
Operating temperature	-10 ... +50 °C (14 ... +122 °F)
Storage temperature	-20 ... +60 °C (-4 ... +140 °F)
Degree of protection	IP65 NEMA 4X
<b>Design</b>	
Weight	1,4 kg (3.0 lb)
Dimensions (W x H x D)	175 x 235 x 92 mm (6.89 x 9.25 x 3.62 inch)
Enclosure material	Polycarbonate
<b>Power supply</b>	
	100 ... 240 V AC @ 15 VA or 11.5 ... 28.5 V DC @ 10 W
<b>Certificates and approvals</b>	
Unclassified locations	UL, UL <sub>C</sub>
Classified locations	
CE	EMC Directive 2004/108/EC ATEX Directive 94/9/EC
C-TICK	

<sup>1)</sup> When used to represent flow rate (PGEN) the frequency can reach as high as 5000 Hz. When used to represent flow total it can reach 50 Hz.

# Flow Measurement

## SITRANS F US Clamp-on

### SITRANS FST020 (Basic)

**Standard MLFB for quick delivery on SITRANS FST020 (Basic)**

#### Selection and Ordering data

Article No.

#### SITRANS FST020 (Basic)

7ME357 - 30 - 0

#### Design

IP65 (NEMA 4X) wall mount

#### Number of channels/ultrasonic paths

Single channel

#### Flowmeter functions and I/O configurations

- With display and 1 additional analog output and SPST relay

#### Meter power options

100 ... 240 V AC

11.5 ... 28.5 V DC, 10 W max

#### Sensor

(includes pipe mounting kit for indicated max. OD listed)  
See "Sensor selection charts" for specifications.

no sensor

A2 universal	Trackmount and straps provided up to 75 mm (3")	A
B3 universal	Trackmount and straps provided up to 125 mm (5")	B
C3 universal	Mounting frame and straps provided up to 300 mm (13")	C
D3 universal	Mounting frame and straps provided up to 600 mm (24")	D
E2 universal	Mounting frame and straps provided up to 1200 mm (48") <sup>1)</sup>	E
For the following A1H to C1H sensors, temperature range is -40 ... 65 °C (-41 ... 150 °F), nominal 21 °C (70 °F)		F
C1H (high precision)	Mounting frame and straps provided up to 1200 mm (48")	M
C2H (high precision)	Mounting frame and straps provided up to 1200 mm (48")	N
D1H (high precision)	Mounting frame and straps provided up to 1200 mm (48") <sup>1)</sup>	P
D4H (high precision)	Mounting frame and straps provided up to 1200 mm (48") <sup>1)</sup>	R

#### Sensor cables

No sensor cable

6 m (20 ft) PVC Jacket (1 pr)

15 m (50 ft) PVC Jacket (1 pr)

30 m (100 ft) PVC Jacket

46 m (150 ft) PVC Jacket

91 m (300 ft) PVC Jacket

#### Approvals

UL, UL<sub>C</sub>, CE, C-TICK

Standard MLFB offering represents 2 to 3 weeks delivery time for quantities under 5.

<sup>1)</sup> Supplied spacer bar supports pipes up to 750 mm (30 inch). For pipes larger than 750 mm (30 inch) purchase also, spare part 7ME3960-0MS40 (1012BN-4).

# Flow Measurement SITRANS F US Clamp-on

## SITRANS FST020 (Basic)

Selection and Ordering data	Article No.	Ord. code
<b>SITRANS FST020 (Basic) IP65 (NEMA 4x)</b>	<b>7ME3570-</b>	
	3 0 - 0	
<b>Number of channels/ultrasonic paths</b>		
Single channel	1	
<b>Flowmeter functions and I/O configurations</b>		
<ul style="list-style-type: none"> <li>With display keypad 1x 4 ... 20 mA, 1x relay, 1x pulse/frequency, 2x digital input</li> </ul>	H	
<b>Meter power options</b>		
100 ... 240 V AC	A	
11.5 ... 28.5 V DC	B	
<b>Sensor for channel 1<sup>1)</sup></b>		
Including pipe mounting tracks for Sizes A & B universal sensors indented for pipe with a OD less than 125 mm (5") and mounting frame/spacer bars for sizes C, D & E universal sensors. Straps provided are for the indicated maximum OD listed below. Strap kits are available to accommodate larger pipes (refer to spare part list). Refer to "Sensor Selection Charts" for the sensor suitability of pipe size and wall thickness		
no sensor		A
A2 universal Trackmount and straps provided up to 75 mm (3")		B
B3 universal Trackmount and straps provided up to 125 mm (5")		C
C3 universal Mounting frame and straps provided up to 330 mm (13")		D
D3 universal Mounting frame and straps provided up to 600 mm (24")		E
E2 universal Mounting frame and straps provided up to 1200 mm (48")		F
For the following A2H to D4H transducers, temperature range is -40 ... 65 °C (-41 ... 150 °F), nominal 21 °C (70 °F)		
A2H (high precision) Trackmount and straps provided up to 75 mm (3")		H
A3H (high precision) Trackmount and straps provided up to 75 mm (5")		J
B1H (high precision) Trackmount and straps provided up to 125 mm (5")		K
B2H (high precision) Trackmount and straps provided up to 125 mm (5")		L
C1H (high precision) up to 600 min (24") with mounting hardware		M
C2H (high precision) up to 600 min (24") with mounting hardware		N
D1H (high precision) Mounting frame and straps provided up to 1200 mm (48") <sup>1)</sup>		P
D2H (high precision) Mounting frame and straps provided up to 1200 mm (48") <sup>1)</sup>		Q
D4H (high precision) Mounting frame and straps provided up to 1200 mm (48") <sup>1)</sup>		R

Selection and Ordering data	Article No.	Ord. code
<b>SITRANS FST020 (Basic) IP65 (NEMA 4x)</b>	<b>7ME3570-</b>	
	3 0 - 0	
High temperature sensor size 2 for up to 230 °C (446 °F) (30 to 200 mm diam. (1 to 8 inch diam.))	Z	P 1 A
High temperature sensor size 3 for up to 230 °C (446 °F) (150 to 610 mm diam. 6 to 24 inch diam.))	Z	P 1 B
High temperature sensor size 4 for up to 230 °C (446 °F) (400 to 1200 mm diam. (16 to 48 inch diam.))	Z	P 1 C
<b>Sensor cables (pair)</b>		
No sensor cable		A
6 m (20 ft) PVC Jacket		B
15 m (50 ft) PVC Jacket		C
30 m (100 ft) PVC Jacket		D
46 m (150 ft) PVC Jacket		E
61 m (200 ft) PVC Jacket		F
91 m (300 ft) PVC Jacket		G
6 m (20 ft) Plenum rated (Teflon jacket)		H
15 m (50 ft) Plenum rated (Teflon jacket)		J
30 m (100 ft) Plenum rated (Teflon jacket)		K
46 m (150 ft) Plenum rated (Teflon jacket)		L
61 m (200 ft) Plenum rated (Teflon jacket)		M
91 m (300 ft) Plenum rated (Teflon jacket)		N
<b>Approvals</b>		
UL, UL <sub>C</sub> , CE, C-TICK		0

<sup>1)</sup> Supplied spacer bar supports pipes up to 1050 mm (42"). For pipes larger than 1050 mm (42") purchase also, spare part 7ME3960-0MS40 (1012BN-4)



# Flow Measurement

## SITRANS F US Clamp-on

### SITRANS FST020 (Basic)

#### Selection and Ordering data

Order code

##### Further designs

Please add "-Z" to Article No. and specify Order code(s).

Cable termination kit (for one cable pair)

- Sensor cable termination for standard and plenum cable

T01

Wet flow transfer calibration (priced on request)

6 point calibration 2/water (Price per channel)

- 2SS40 pipe
- 3CS40 pipe
- 4CS40 pipe
- 4SS40 pipe
- 6CS40 pipe
- 6SS40 pipe
- 6CS120 pipe
- 8CS40 pipe
- 8SS40 pipe
- 8CS120 pipe
- 10CS Standard pipe
- 10CS40 pipe
- 10SS40 pipe
- 12CS Standard pipe
- 12CS40 pipe
- 14CS30 pipe
- 14CS40 pipe
- 16CS Standard pipe
- 16CS40 pipe
- 18CS Standard pipe
- 20CS20 pipe
- 20CS30 pipe
- 24CS Standard pipe
- 24CS20 pipe
- 24CS30 pipe
- 30CS Standard pipe
- 36CS Standard pipe
- Other pipe, other liquid, additional points, witness

D01  
D02  
D03  
D04  
D05  
D06  
D07  
D08  
D09  
D10  
D11  
D12  
D13  
D14  
D15  
D16  
D17  
D18  
D19  
D20  
D21  
D22  
D23  
D24  
D25  
D26  
D27  
Y28

Tag name plate

- Stainless steel tags with 3.2 mm (0.13 inch) character size (68 characters max.)

Y19

#### MLFB example

##### Application example

A basic clamp-on meter is required for a DN 150 (6" schedule 40) carbon steel waste water line, with a pipe wall thickness of 7.1 mm (0.28"). Meter electronics are to be located in an instrumentation shed with available AC power. 36 m (120 ft) of sensor cable is needed to reach pipe location.

MLFB Article No.: **7ME3570-1HA300-ONE0**


#### Selection and Ordering data

Article No.

Ord. code

##### SITRANS FST020 meter family

- IP65 (NEMA 4X) enclosure
- Single channel
- Standard I/O option
- 100 ... 240 V AC power option
- Sensor code for channel 1
- 46 m (150 ft) sensor cable



#### Selection and Ordering data

Order code

##### Operating Instructions for SITRANS FST020

- English NEMA 4X
- German NEMA 4X

A5E03086487  
A5E03086488

This device is shipped with a Quick Start Guide and a CD containing further SITRANS F literature.

All literature is also available for free at:

<http://www.siemens.com/flowdocumentation>

#### Universal sensor selection chart IP68

##### Based on pipe size (pipes other than steel)

Pipe size	Order Code	Outer diameter range (mm)		Outer diameter range (inch)	
		min.	max.	min.	max.
A2	B	12,7	50,8	0,5	2
B3	C	19	127	0,75	5
C3	D	51	305	2	12
D3	E	203	610	8	24
E2	F	254	6096	10	249

#### High precision sensor selection chart IP68

##### Based on pipe wall thickness (steel pipes only)

Pipe Wall	Order Code	Pipe Wall [mm]		Pipe Wall [inch]	
		min.	max.	min.	max.
A1H	G	0,64	1,02	0,025	0,04
A2H	H	1,02	1,52	0,04	0,06
A3H	J	1,52	2,03	0,06	0,08
B1H	K	2,03	3,05	0,08	0,12
B2H	L	3,05	4,06	0,12	0,16
C1H	M	4,06	5,84	0,16	0,23
C2H	N	5,84	8,13	0,23	0,32
D1H	P	8,13	11,18	0,32	0,44
D2H	Q	11,18	15,75	0,44	0,62
D4H	R	15,75	31,75	0,62	1,25